

OUR PLUMBERS HAVE THE BEST PEX™

We believe that hassle-free plumbing shouldn't be a pipe dream. Combining fit-out versatility with durability, TradePex pipes make your job easier without compromising on quality. Featuring all brass fittings with extra options, TradePex stands above the rest. Sleeve it, Crimp it, Done.

HYDRONIC PIPE SPECIFICATIONS (ORANGE)

TUBING

1. All tubing is 5-layer PE-RT, with the layers consisting of the following:
 - a. Inner PE-RT layer
 - b. Adhesive layer
 - c. EVOH layer
 - d. Adhesive layer
 - e. Outer PE-RT layer
2. Pipe is rated for continuous operation of 1400 KPa @ 20°C and 700 KPa at 80°C
3. The EVOH layer limits oxygen diffusion through the pipe to less than 0.32 mg/(m²/d) @ 40°C water temperature.
4. Temperature range -20 °C to +95 °C
5. The minimum bend radius for cold bending of the tubing shall be no less than six (6) times the outside diameter. Bends with a smaller radius shall require the use of manufacturer supplied metal bend supports.

STORAGE

1. Store materials in dry, enclosed, well-ventilated area protected from exposure to harmful environmental conditions.
2. PE-RT tubing and manifold openings shall be covered or capped to prevent contaminants from entering.
3. Do not expose PE-RT tubing to direct sunlight for more than 30 days.

tradepex.com.au

Available exclusively at Tradelink Plumbing Centres
1800 PLUMBING

TradePex™